



ATLAS ESKIMO

Setting accelerator for renders and paints

- enables rendering and painting at 0°C and in high air humidity (above 80%)
- accelerates coat setting time
- gives early resistance to rain
- neutral to other material properties

Properties

Accelerates water evaporation from the applied render or paint – accelerates the first stage of setting of dispersion products – water evaporation from the applied material. Therefore, the second stage, consisting in binder setting and drying, can start earlier – the applied material gets resistant to rapid temperature drop and precipitation earlier (already after approx. 6 - 8 hours).

Easy in use – ready-to-use liquid admixture dosed directly to material before application on a façade; easily mixing with rendering mass or paint.

Neutral to other properties of material – does not lead to deterioration of durability or operational parameters after setting.

Does not change the colour of the applied render or paint coat.

ATLAS ESKIMO is manufactured as yellow liquid of smell of ammonia

Use

Enables rendering and painting at 0°C – recommended during façade works in low temperature (0 – 10°C) and high air humidity (above 80%)

Types of modified materials:

- ATLAS ACRYLIC renders
- ATLAS SILICONE renders
- ATLAS SALTA E acrylic paints
- ATLAS SALTA, ATLAS SALTA N, ATLAS SALTA N PLUS silicone paints

Technical data

Relative density	approx. 1,1 g/cm ³
Temperature of use	from 0°C to +10°C

Agent use

The agent is added to render or paint directly before their application. It is recommended to observe the weight ratio of 1%, i.e. up to 0.25 kg (whole bottle) with 25 kg of render and up to 0.15 kg (3/5 of a bottle) with 10 l of paint. After thorough manual or machine mixing, the material can be applied.

Packaging

Plastic bottle of 0.25 kg

Safety information

Safety information is provided on the product packaging and in the Safety Data Sheet available at www.atlas.com.pl.

Storage and transport

Information on storage and transport is provided on the product packaging and in the Material Safety Data Sheet available at www.atlas.com.pl.

The shelf life of the product (use-by-date) is 18 months from the date of manufacture on the packaging.



Important additional information

The substrate for render or paint must not be frozen. Recommended application and drying temperature from 0°C up to +10°C. Freshly applied material gets resistant to precipitation after approx. 6 – 8 hours, depending on ambient temperature and humidity

The tools must be cleaned with clean water directly after use

The information included in the Product Data Sheet constitutes basic guidelines concerning the use of the product and does not release from the obligation to conduct work according to the best construction practices and health and safety at work regulations. On the date of issue of this Product Data Sheet, all previous Product Data Sheets become invalid. The accompanying documents for the product are available at www.atlas.com.pl.

The content of the Product Data Sheet as well as the symbols and trade names used in it are the property of Atlas sp. z o. o. Their unauthorized use will be sanctioned.

Date of update: 2022-03-02

